


# DKM8

DIN Rail Terminal Blocks > Stud Connection

Date:2025-11-03Version:1.2





The web catalog is for reference only. Dinkle remains the right of product modification and engineering change of the design.

The final product is made according to engineering drawing.

#### **Product Description**

M8, 1000V, 150A, Beige (default)

#### General information

Short description	DIN Rail terminal blocks, Stud Connection
Category	Feed-Through single level
Color	Beige (default)
Connection method	Stud Connection
Type of locking	Rail Mounting
Length (mm)	67
Width (mm)	21
Height (mm)	63
Level	Single level
Connection points	1

#### Material information

Insulation material	PA
Insulation material group	I
Flame retardant rating , compliant with UL94	VO
Insulation resistance	□500MΩ at DC 500V

#### Connection data-IEC

Rated voltage (V)	1000
Rated current (A)	150
Rated voltage (III/3)(V)	1000
Rated impulse voltage (III/3)(KV)	8
Conductor cross section solid. min (mm²)	2.5
Conductor cross section solid.max (mm²)	50
Conductor cross section stranded. min (mm²)	2.5
Conductor cross section stranded. max (mm²)	50
Screw thread	M8
Recommend tightening torque. min (N.m)	6
Recommend tightening torque. max (N.m)	12
Mounting rail	TS-35
End cover plate required	NO
Grounding connections	NO

#### Connection data-UL

Rated voltage (UL/CUL Group E)(V)	1000
Rated current (UL/CUL Group E)(A)	150
Min. solid wire connection (AWG) acc. to UL/CUL	14
Max. solid wire connection AWG acc. to UL/CUL	1/0

## Environment & Safety

Back of the hand protection (YES or NO)	NO
Finger protection (YES or NO)	NO
Operating temperature. max (°C)	120
Operating temperature. min (°C)	-40

### **UL** Recognized

Wire Range (Group E)(AWG)	14~1/0
Rated voltage (Group E)(V)	1000
Rated current (Group E)(A)	150


### **CUL** Recognized

	Wire Range (Group E)(AWG)	14~1/0
--	---------------------------	--------



Rated voltage (Group E)(V)	1000
Rated current (Group E)(A)	150

### Drawings



# Approvals





