


# EC116CV-XXP

PCB Terminal Blocks > PCB Connector-Plug

Date:2026-05-09



The web catalog is for reference only. Dinkle remains the right of product modification and engineering change of the design. The final product is made according to engineering drawing.

## Product Description

Pitch : 10.16mm, 300V, 51A

## General information

|                                        |                                    |
|----------------------------------------|------------------------------------|
| Short description                      | PCB Connector-Plug, Wave soldering |
| Category                               | PCB Connector – Plug               |
| Pitch (mm)                             | 10.16                              |
| Color                                  | Green (default)                    |
| Type of locking                        | Without                            |
| Soldering method                       | Wave soldering                     |
| Length (mm)                            | $10.16 \times (P-1) + 10.96$       |
| Width (mm)                             | 13.6                               |
| Height (mm)                            | 32.1                               |
| Pin demensions (Thickness x Width)(mm) | 0.8x1.2                            |
| PCB hole diameter (mm)                 | 1.8                                |
| Number of positions                    | 02P~10P                            |
| Level                                  | Single level                       |

## Material information

|                     |    |
|---------------------|----|
| Insulation material | PA |
|---------------------|----|

|                                              |                   |
|----------------------------------------------|-------------------|
| Insulation material group                    | I                 |
| Flame retardant rating , compliant with UL94 | V0                |
| Insulation resistance                        | ≥500MΩ at DC 500V |
| Conductor material                           | COPPER ALLOY      |
| Plating of conductor surface                 | Ag PLATED         |

### Connection data-IEC

|                                   |      |
|-----------------------------------|------|
| Rated voltage (V)                 | 1000 |
| Rated current (A)                 | 76   |
| Rated voltage (II/2)(V)           | 1000 |
| Rated voltage (III/2) (V)         | 1000 |
| Rated voltage (III/3)(V)          | 630  |
| Rated impulse voltage (II/2)(KV)  | 8    |
| Rated impulse voltage (III/2)(KV) | 8    |
| Rated impulse voltage (III/3)(KV) | 8    |

### Connection data-UL

|                                   |     |
|-----------------------------------|-----|
| Rated voltage (UL/CUL Group B)(V) | 300 |
| Rated current (UL/CUL Group B)(A) | 51  |
| Rated voltage (UL/CUL Group C)(V) | 300 |
| Rated current (UL/CUL Group C)(A) | 51  |
| Rated voltage (UL/CUL Group D)(V) | 600 |
| Rated current (UL/CUL Group D)(A) | 5   |

### Environment & Safety

|                                 |     |
|---------------------------------|-----|
| Finger protection (YES or NO)   | YES |
| Operating temperature. max (°C) | 120 |
| Operating temperature. min (°C) | -40 |

### UL Recognized


|                            |     |
|----------------------------|-----|
| Rated voltage (Group B)(V) | 300 |
| Rated current (Group B)(A) | 51  |
| Rated voltage (Group C)(V) | 300 |
| Rated current (Group C)(A) | 51  |
| Rated voltage (Group D)(V) | 600 |

|                            |   |
|----------------------------|---|
| Rated current (Group D)(A) | 5 |
|----------------------------|---|

## CUL Recognized

|                            |     |
|----------------------------|-----|
| Rated voltage (Group B)(V) | 300 |
| Rated current (Group B)(A) | 51  |
| Rated voltage (Group C)(V) | 300 |
| Rated current (Group C)(A) | 51  |
| Rated voltage (Group D)(V) | 600 |
| Rated current (Group D)(A) | 5   |

## Drawings



## Approvals

