



# DPH2.5

DIN Rail Terminal Blocks > Push-in Design

Date:2025-11-04





The web catalog is for reference only. Dinkle remains the right of product modification and engineering change of the design.

The final product is made according to engineering drawing.

### **Product Description**

600V, 20A, Beige (default)

#### General information

Short description	Single level Feed-Through Terminal Block, Push-in Design
Category	Single level Feed Through Terminal Block
Color	Beige (default)
Connection method	Push-in Design
Type of locking	Rail Mounting
Length (mm)	61
Width (mm)	5.1
Height (mm)	37.4/ 38.9 ( TS-35N ) /46.4 ( TS-35/15N )
Level	Single level
Connection points	2


#### Material information


Insulation material	PA
Insulation material group	I
Flame retardant rating , compliant with UL94	V0



Insulation resistance	≥500MΩ at DC 500V
Connection data-IEC	
Rated voltage (V)	800
Rated current (A)	24
Rated voltage (III/3)(V)	800
Rated impulse voltage (III/3)(KV)	8
Conductor cross section solid. min (mm²)	0.14
Conductor cross section solid.max (mm²)	4
Conductor cross section stranded. min (mm²)	0.14
Conductor cross section stranded. max (mm²)	2.5
Conductor cross section flexible, with min ferrule without plastic sleeve (mm²)	0.25
Conductor cross section flexible, with max ferrule without plastic sleeve (mm²)	2.5
Conductor cross section flexible, with min ferrule with plastic sleeve (mm²)	0.25
Conductor cross section flexible, with max ferrule with plastic sleeve (mm²)	2.5
2 conductors with same cross section flexible, min twin ferrules with plastic sleeve (mm²)	0.5
2 conductors with same cross section flexible, max twin ferrules with plastic sleeve (mm²)	0.5
Slotted screwdriver size (Blade thickness x Width)(mm)	0.6x3.5
Stripping Length (mm)	10~11
Mounting rail	TS-35N \ TS-35/15N
End cover plate required	YES
Grounding connections	NO
Connection data-UL	
Rated voltage (UL/CUL Group B)(V)	600
Rated current (UL/CUL Group B)(A)	20
Rated voltage (UL/CUL Group C)(V)	600
Rated current (UL/CUL Group C)(A)	20
Rated current (UL/CUL Group D)(A)	600
Rated voltage (UL/CUL Group E)(V)	5
Min. solid wire connection (AWG) acc. to UL/CUL	26
Max. solid wire connection AWG acc. to UL/CUL	12

	26
Max. stranded wire connection AWG acc. to UL/CUL	12
Environment & Safety	
Back of the hand protection (YES or NO)	YES
Finger protection (YES or NO)	YES
Operating temperature. max (°C)	120
Operating temperature. min (°C)	-40
JL Recognized	
Wire Range (Group B)(AWG)	26~12
Rated voltage (Group B)(V)	600
Rated current (Group B)(A)	20
Wire Range (Group C)(AWG)	26~12
Rated voltage (Group C)(V)	600
Rated current (Group C)(A)	20
Wire Range (Group D)(AWG)	26~12
Rated voltage (Group D)(V)	600
Rated current (Group D)(A)	5
CUL Recognized	
CUL Recognized Wire Range (Group B)(AWG)	26~12
-	26~12 600
Wire Range (Group B)(AWG)	
Wire Range (Group B)(AWG)  Rated voltage (Group B)(V)	600
Wire Range (Group B)(AWG)  Rated voltage (Group B)(V)  Rated current (Group B)(A)	600 20
Wire Range (Group B)(AWG)  Rated voltage (Group B)(V)  Rated current (Group B)(A)  Wire Range (Group C)(AWG)	600 20 26~12
Wire Range (Group B)(AWG)  Rated voltage (Group B)(V)  Rated current (Group B)(A)  Wire Range (Group C)(AWG)  Rated voltage (Group C)(V)	600 20 26~12 600
Wire Range (Group B)(AWG)  Rated voltage (Group B)(V)  Rated current (Group B)(A)  Wire Range (Group C)(AWG)  Rated voltage (Group C)(V)  Rated current (Group C)(A)	600 20 26~12 600 20





## Approvals





