


2EHDRSM-XXP

PCB Terminal Blocks > Special Type Terminal Blocks

Date:2025-11-02Version:V1





The web catalog is for reference only. Dinkle remains the right of product modification and engineering change of the design.

The final product is made according to engineering drawing.

Product Description

Pitch: 5.08 mm, 300V, 12/15A

General information

Short description	Special type terminal blocks, Screw connection
Category	Special type terminal blocks
Pitch (mm)	5.08
Color	Green (default)
Connection method	Screw connection
Type of locking	With lock flange
Length (mm)	5.08*(P-1)+15
Width (mm)	20.50
Height (mm)	17.3
Number of positions	02~20P

Material information

Insulation material	PA
Insulation material group	I
Flame retardant rating , compliant with UL94	VO
Conductor material	COPPER ALLOY



Plating of conductor surface	Tin PLATED	
Connection data-IEC		
Rated voltage (V)	630	
Rated current (A)	18	
Rated voltage (II/2)(V)	600	
Rated voltage (III/2) (V)	320	
Rated voltage (III/3)(V)	250	
Rated impulse voltage (II/2)(KV)	4	
Rated impulse voltage (III/2)(KV)	4	
Rated impulse voltage (III/3)(KV)	4	
Conductor cross section solid. min (mm²)	0.5	
Conductor cross section solid.max (mm²)	2.5	
Conductor cross section stranded. min (mm²)	0.5	
Conductor cross section stranded. max (mm²)	2.5	
Conductor cross section flexible, with min ferrule without plastic sleeve (mm²)	0.25	
Conductor cross section flexible, with max ferrule without plastic sleeve (mm²)	2.5	
Conductor cross section flexible, with min ferrule with plastic sleeve (mm²)	0.25	
Conductor cross section flexible, with max ferrule with plastic sleeve (mm²)	1.5	
2 conductors with same cross section, solid, max (mm²)	1.5	
2 conductors with same cross section, stranded, max (mm²)	1.5	
2 conductors with same cross section flexible, with min ferrule without plastic sleeve (mm²)	0.25	
2 conductors with same cross section flexible, with max ferrule without plastic sleeve (mm²)	0.75	
2 conductors with same cross section flexible, min twin ferrules with plastic sleeve (mm²)	0.5	
2 conductors with same cross section flexible, max twin ferrules with plastic sleeve (mm²)	1.5	
Screw thread	M2.5	
Slotted screwdriver size (Blade thickness x Width)(mm)	0.6x3.5	
Philips screwdriver size	PH1	
Rated torque (N.m)	0.75	
Stripping Length (mm)	7~8	

Connection data-UL

Rated voltage (UL/CUL Group B)(V)	300
Rated current (UL/CUL Group B)(A)	12/15

Environment & Safety

Back of the hand protection (YES or NO)	YES
Finger protection (YES or NO)	YES
Operating temperature. max (°C)	115
Operating temperature. min (°C)	-40


UL Recognized


Wire Range (Group B)(AWG)	28~12
Rated voltage (Group B)(V)	300
Rated current (Group B)(A)	12/15

CUL Recognized

Wire Range (Group B)(AWG)	28~12
Rated voltage (Group B)(V)	300
Rated current (Group B)(A)	12/15

Drawings





Approvals







