


# 0401-0051

非網管型乙太網交換機



Safety Standards



## Specification

IEEE Standard	IEEE 802.3 10Base-T Ethernet IEEE 802.3u 100Base-TX Fast Ethernet IEEE802.3x Flow Control and Back Pressure
Switch Architecture	Back-plane (Switching Fabric): 1Gbps
Data Processing	Store and Forward
Flow Control	IEEE 802.3x Flow Control and Back Pressure
MAC Address Table Size	1K
Packet Buffer Size	448Kbits
Network Connector	5xRJ-45 10/100BaseT(X) auto negotiation, Auto MDI/MDI-X function, Full/Half duplex
Network Cable	UTP/STP Cat.5e or above Cable EIA/TIA-568 (100m)
Protocol	CSMA/CD
LED	PW1(Power 1) Green PW2(Power 2) Green ON: Power is detected OFF: Power is not detected  TX/RJ-45 port: LNK (Link/Active) Green ON: TX port is detected Flashing: TX data is transmitting/receiving


## Specification

Reserve polarity protection	Present
Overload current protection	Present
Power Supply	Redundant Dual DC 12V-56V Power Input
Power Consumption	2.24W@48 VDC full load without PoE
Removable Terminal Block	Provide 2 Redundant power, 4 Pin Wire range: 0.34mm^2 to 2.5mm^2 Solid wire (AWG): 12-28 Stranded wire (AWG): 12-30 Torque:5lb-In/0.5Nm Wire Strip length: 7-8mm
Operating Temperature	-40°C to 75°C
Operating Humidity	5% to 95% (Non-condensing)
Storage Temperature	-40°C to 85°C
MTBF (mean time between failure)	582,558.91 hrs (Telcordia (Bellcore), GB) at 50°C
Housing	Rugged Metal, IP30 protection
Case Dimension (L x W x H)	103.5 x 32 x 81.5 mm (L x W x H)
Installation	DIN Rail Mount or Wall Mount

## Certifications

Safety	UL 60950-1
Safety	LVD (EN62368-1)
EMC	CE, FCC, EN 55032/35
EMI	CISPR 32, FCC Part 15B Class A
EMS	IEC 61000-4-2 ESD: Contact: 6KV; Air: 8KV
	IEC 61000-4-4 EFT: Power: 2KV; Signal: 2KV
	IEC 61000-4-5 Surge: Power: 2KV; Signal: 2KV
Vibration	EN 60068-2-6
Shock	EN 60068-2-27
Free Fall	EN 60068-2-32

LED indicator



# Dimensions

L X W X H : 103.5 x 32 x 81.5

